



Air Shower with High Speed shutter doors

Large Air Shower will be used high speed shutter doors, which is fast to open and close the doors, and save the space.

Normally, it is used for passing materials and forklift.

Motor of high speed shutter door: 0.8KW "SEW" brand

Controller of high speed shutter doors: PLC inverter, which is easy for operating

Material for door curtain:PVC curtain

Details of Air Shower with High Speed Shutter Doors



Cargo Air Shower Tunnel with High Speed Shutter Doors



Radar sensor for opening door



Available color for fabric door curtain

Color: Grey/Blue/Red/Orange
/Yellow

www.cleanroom-airshower.com

Cargo Air Shower Tunnel with High Speed Shutter Doors



LED Lamp



360 degree rotatable
SS304 Nozzles



Cargo Air Shower Tunnel with High Speed Shutter Doors



Size and Specifications:

Model	Air shower with high speed shutter doors			
	AS-2500D-2-SD	AS-2600D-2-SD	AS-3000D-3-H2.8-SD	AS-3000D-3-H3.2-SD
External dimensions WxDxH(mm)	2500x2000x2300	2600x2000x2800	3000x3000x2800	3000x3000x3200
Internal dimensions WxDxH(mm)	2000x2000x2000	2000x2000x2500	2400x3000x2500	2400x3000x2900
Material	1. powder coated steel for outside and Stainless steel for inside,2 Full stainless steel			
Doors	High speed shutter doors 0.8KW x2 sets			
Suitable for	Materials and forklifts			
Nozzles	32(2- side)	32(2- side)	48(2-side)	48(2-side)
Blower fan	#4250x4 set	#4250 x 4 sets	#4250x6sets	#4250x6sets
Blow power(W)	4200W	4200W	6600W	6600W
HEPA filter's dimensions	610x610x69mm 4pcs	915x610x69 mm 4pcs	915x610x69 mm 6pcs	915x610x69 mm 6 pcs
G3 Primary filter	4 pcs	4 pcs	6 pcs	6 pcs
Nozzle	Material:Stainless steel, Diameter 27mm			
Air shower time	0~99s Adjustable			
Spurt wind speed	20~25m/s			
Voltage	AC380V/50Hz/3Ph			
Filter efficiency	Above 99.99% efficiency on 0.3um particles			
Control system	IC control panel, electronic interlock and automatic blowing			

Customized sizes can be accepted